## (19) World Intellectual Property Organization International Bureau





(43) International Publication Date 15 February 2001 (15.02.2001)

## (10) International Publication Number WO 01/11426 A1

(51) International Patent Classification7: 7/16, H05K 3/12, B41M 3/00

G03F 1/00.

(74) Agents: COZENS, Paul, Dennis et al.; Mathys & Squire, 100 Gray's Inn Road, London WC1X 8AL (GB).

(21) International Application Number: PCT/GB00/02077

- (22) International Filing Date: 30 May 2000 (30.05.2000)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

9912437.2

27 May 1999 (27.05.1999) GB

- 0005929.5 10 March 2000 (10.03,2000) GB
- (71) Applicant (for all designated States except US): PAT-TERNING TECHNOLOGIES LIMITED [GB/GB]: Unit 7, The Maltings, Green Drift, Royston, Hertfordshire SG8 5DY (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): SPEAKMAN, Stuart [GB/GB]; 7 Chapel Drive, Little Waltham, Chelmsford, Essex CM3 3LW (GB).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR,
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

## Published:

- With international search report.
- With amended claims and statement.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF FORMING A MASKING PATTERN ON A SURFACE

(57) Abstract: A method of forming a masking pattern on a surface using the technique of droplet ejection to deposit droplets of deposition material, said method comprising depositing a plurality of droplets on said surface to form such a pattern comprising multiple discrete or coalesced extended portions.